

OvisLink



SF-401 SOHO Firewall Gateway with 1-WAN Port/ 4Nway Switch Ports

Specifications

Protocols	
IP, NAT+, RIP1, RIP2, ARP, ICMP, DHCP client/server, PPPoE, PPP, IPSec, PPTP	
Management	
Web configuration	
Local LAN	
4 ports 10/100Base-T N-way Ethernet Switching	
Internet	
10/100Base-T N-way Ethernet port to external Cable/DSL Modem, or other network equipment	
MDIX/MDI Buttons	
One for local uplink, the other for Cable/DSL modem connectivity	
Mini-firewall	
An effective business-class firewall against hackers and Denial-of-Service attacks. SPI, Real time alert, Schedule, Trusted host, web patrol.	
Firmware	
Embedded FTP Server for firmware upgrade, Embedded FTP Server configuration backup and restore	
Security	
PAP, CHAP, NAT, Port forwarding with NAT, DMZ	
NAT Implementation	
NetMeeting, CuSeeMe, MS PPTP client and reaceroute, Real Audio, ICQ, VDOLive, IRC, Quake, Quake variants, and other popular games, Port forwarding	
LED Indicators	
Power/Erro	Green/Red
Local x 4 100/10	Green/Orange
Internet 100/10	Green/Orange
Havemail	Green
Electronic Specifications	
Input Power: DC 5V, @2.4A	
Agency and Regulatory: FCC part 15 Class B, VCCI, CE	
Physical Dimension: 160 x 105.4 x 27 mm3 (L x W x H)	
Weight: 218g	
Operating Temperature: 0 °C to 50 °C	
Operating Humidity: 0-90% non-condensing	