

OvisLink

SR500

4 Port Broadband Routers



Sharing for Hi-speed Surfing

No need to apply for additional IP address or account, multi-users can share just one this device, single IP address, and one Cable/xDSL Modem for Internet surfing concurrently.

Plug & Play

Both DHCP client and server can complete the network configuration for the device self and all computers on local network automatically. Zero configuration effort is needed for users. Especially the 4 port Ethernet Switch design, users can just plug the cable into the device without buying additional Hub/Switch.

Incoming Mail Indication

This product can check incoming mail for user periodically. User can power on his computer to collect and read mail until this product blinks the mail LED.

Features

- * Web UI management.
- * Support PPPoE.
- * Support VPN(PPTP, IP sec pass thru)
- * LED indicator for received E-Mail.
- * Up to 8Mbps performance.
- * Support Auto MDIX for both LAN/WAN port uplink.
- * Internet applications such as Web browser, ICQ, FTP, Telnet, E-Mail, AoE, News, NetMeeting, Ping, mIRC, AOE, PCAnyWhere.....
- * DHCP server allocates up to 253 client IP addresses.
- * Static DHCP.
- * Proxy DNS.
- * Dynamic DNS.
- * Virtual server.
- * DMZ host & Multi-DMZ.
- * Rich Packet Filters.
- * Static routing.
- * Installation wizard.
- * Allow firmware upgrade through network.
- * Support Windows98/ME/NT/2000/XP, Unix, and Mac.
- * Natural firewall keeps hackers out.
- * Load/save device setting from/to a PC file
- * Event log.

Specifications

- Protocols
- * IP, NAT, ARP, ICMP, DHCP client/server, PPPoE, PPP, PAP, CHAP, NTP, HTTP, TFTP, POP3.
- Management
- * Telnet through network.
 - * GUI program for Windows 95/98/ME/NT/2000/XP through network.
- Local
- * 4 ports 10/100Base-T N-way Ethernet Switching.
- Internet
- * 10/100Base-T N-way Ethernet port to external Cable/DSL Modem, or other network equipment.
- LED Indicators
- * Power/Error Green/Red
 - * Local x 4 100/10 Green/Orange
 - * Internet 100/10 Green/Orange
 - * Have Mail Green
- Electronic Specifications
- Input Power: DC 5V, @2.4A
- Agency and Regulatory: CE, FCC part 15 Class B, BSMI, VCCI
- Physical Dimension: 160 x 105.4 x 27 mm3(L x W x H)
- Weight: 218g
- Operating Temperature: 0C to 50C
- Operating Humidity: 0-90% non-condensing